

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	24MAR2015	DW	CW
	B	ECR-15-018270	07DEC2015	DW	CW

NOTES:

- TECHNICAL CHARACTERISTICS:
INSULATION MATERIAL: PC
RATED VOLTAGE: 50V
RATED CURRENT: 5A
INSULATION RESISTANCE: $\geq 400M\Omega$
RATED IMPULSE VOLTAGE: 0.8KV
POLLUTION DEGREE: 3
FLAMMABILITY: UL94V-0
MATING CYCLES: 500 CYCLES
OPERATION TEMPERATURE: $-40\sim+125^{\circ}C$
WIRE RANGE: $0.08\sim 0.52\text{ mm}^2$ (28~20 AWG)
CONTACT TYPE: CRIMP CONTACT
- CONTACT NEED TO BE ORDERED SEPARATELY.
(ORDER No. REFER TO DRAWING: T20700X10XX000)

注释:

- 技术参数:
绝缘材料: PC
额定电压: 50V
额定电流: 5A
绝缘电阻: $\geq 400M\Omega$
额定脉冲电压: 0.8KV
污染等级: 3
阻燃等级: UL94V-0
插拔次数: 500次
工作温度: $-40\sim+125^{\circ}C$
接线范围: $0.08\sim 0.52\text{ mm}^2$ (28~20 AWG)
接线类型: 冷压接
- 端子需要单独订购.
(订货号参考图面: T20700X10XX000)

HMN-009-M	T2111092101-000
DESCRIPTION	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED:
mm	
	0 PLC \pm
	1 PLC \pm
	2 PLC \pm
	3 PLC \pm
	4 PLC \pm
	ANGLES \pm
MATERIAL	FINISH
-	-
-	-

DWN	24MAR2015
David Wang	
CHK	24MAR2015
Chris Wang	
APVD	24MAR2015
Xiang Xu	
PRODUCT SPEC	108-137064
APPLICATION SPEC	114-137064
WEIGHT	-
Customer Drawing	

TE Connectivity		NAME		RESTRICTED TO
		HMN-009-M		
SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO	
A3	00779	T2111092101000	-	
SCALE		SHEET	OF	REV
3:2		1	1	B

1470-19 (3/13)