

Housing - VC-MEMV-T4-R - 1855160

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Metal sleeve housing, EMC-coating, locking screws with knurled head, with conductive seal, type 4, cable screw connection Pg21

The illustration shows version VC-MEMV-T3-R



Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	420.7 GRM
Custom tariff number	85389099
Country of origin	Poland

Technical data

Dimensions

Height	75 mm
Width	33 mm
Length	104 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 125 °C
---------------------------------	-------------------

General

Type	VC4
Color	nickel
Locking type	Screw locking, knurled head
Tightening torque, mounting screw	1 Nm \pm 0.5 Nm
No. of cable outlets	1
Cable exit	Angled
Screw connection	none
Type of the screw connection	Pg21

Housing - VC-MEMV-T4-R - 1855160

Technical data

General

Housing material	Zinc die-cast, surface bronzed and nickel-plated
Housing surface material	Nickel-plated
Seal material	EPDM, conductive
Material of locking screw	Nickel-plated brass

Classifications

eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27140816
eCl@ss 5.0	27371205
eCl@ss 5.1	27371205
eCl@ss 6.0	27371205
eCl@ss 7.0	27371205
eCl@ss 8.0	27440202

ETIM

ETIM 2.0	EC000437
ETIM 3.0	EC000437
ETIM 4.0	EC000437
ETIM 5.0	EC000437

UNSPSC

UNSPSC 6.01	31261502
UNSPSC 7.0901	31261502
UNSPSC 11	31261502
UNSPSC 12.01	31261502
UNSPSC 13.2	31261502

Approvals

Approvals

Approvals

GOST


Ex Approvals

Housing - VC-MEMV-T4-R - 1855160

Approvals

Approvals submitted

Approval details



Drawings

Dimensioned drawing

