


Coaxial contacts for cable applications

Identification	Impedance (Ω)	Part number			
		Straight male contacts		Straight female contacts	
		Performance level 3	S4 ¹⁾	Performance level 3	S4 ¹⁾
Solder / crimp contact for cables RG 174 U, 188 AU, 316 U for cables RG 178 BU, 196 AU, 404 U for cables RG 58 CU, 141 AU for cables RG 179 BU, 187 AU for cables RGD 179	50	09 69 281 7140	09 69 281 5140	09 69 181 7140	09 69 181 5140
	50	09 69 281 7141	09 69 281 5141	09 69 181 7141	09 69 181 5141
	50	09 69 281 7143	09 69 281 5143	09 69 181 7143	09 69 181 5143
	75	09 69 281 7230	09 69 281 5230	09 69 181 7230	09 69 181 5230
	75	09 69 281 7233	09 69 281 5233	09 69 181 7233	09 69 181 5233
Crimp / crimp contact for cables RG 174 U, 188 AU, 316 U for cables RG 179 BU, 187 AU for cables RG 59 for cables RGD 179	50	09 69 282 7140	09 69 282 5140	09 69 182 7140	09 69 182 5140
	75	09 69 282 7230	09 69 282 5230	09 69 182 7230	09 69 182 5230
	75	09 69 282 7232	09 69 282 5232	09 69 182 7232	09 69 182 5232
	75	09 69 282 7233	09 69 282 5233	09 69 182 7233	09 69 182 5233

Harnessing dimensions (mm)



Part number	Ø A	Ø B	Ø C	Ø D	E	F	G
09 69 181 x140 09 69 281 x140	0.85	1.9	2.3	3.2	9.5	5.0	3.0
09 69 181 x141 09 69 281 x141	0.85	1.2	1.4	2.3	9.5	5.0	3.0
09 69 181 x143 09 69 281 x143	1.00	3.0	4.4	5.2	9.5	5.0	3.0
09 69 181 x230 09 69 281 x230	0.50	1.9	2.3	3.2	9.5	5.0	3.0
09 69 182 x140 09 69 282 x140	0.60	1.9	2.4	3.2	9.0	5.0	3.0
09 69 182 x230 09 69 282 x230	0.60	1.9	2.4	3.2	9.0	5.0	3.0
09 69 182 x232 09 69 282 x232	0.95	3.8	5.1	6.2	9.0	4.3	3.7
09 69 181 x233 09 69 281 x233	0.50	1.9	2.6	3.5	9.5	5.0	3.0
09 69 182 x233 09 69 282 x233	0.60	1.9	2.6	3.5	9.3	4.3	3.0

¹⁾ S4 = 0.76 µm Au or PdNi equivalent
Dimensions see pages 05.75 and 05.76
Tooling see chapter 20