

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C
	OPERATING&STORAGE HUMIDTY RANGE	85%MAX	APPLICABLE CABLE	CABLE DIAMETER : φ6.4~7.8
	VOLTAGE			
	CURRENT			

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
------	-------------	--------------	----	----

CONSTRUCTION

GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X

--	--	--	--	--

COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
1	DIS-E-003060	TM. ONO	KN. ICHIKAWA	09. 12. 14

REMARK △ THIS PRODUCT SHALL BE MATED WITH DH3 * B-27S, IT APPLIES TO DH3 * B-27S ABOUT A MECHANICAL, ENVIRONMENTAL CHARACTERISTICS. Unless otherwise specified, refer to JIS C 5402.	APPROVED	KN. ICHIKAWA	09. 11. 17
	CHECKED	KN. ICHIKAWA	09. 11. 17
	DESIGNED	MO. SHIMOYAMA	09. 11. 17
	DRAWN	TM. ONO	09. 11. 17

Note QT:Qualification Test AT:Assurance Test X:Applicable Test	DRAWING NO.	ELC4-126587-00
--	-------------	----------------

HRS	SPECIFICATION SHEET	PART NO.	DH-27-CV1B	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL244-0010-5-00	△ 1/1