



- NOTES:**
- MATERIALS:
 HOOD: PBT GF UL94 V-0 BLACK
 FRONTSEALING: SILICONE VMQ BLUE
 SCREW: STAINLESS STEEL
 O-RING: NBR BLACK
 - TEMPERATURE RANGE: -30°C TO +90°C
 - RECOMMENDED TORQUE FOR SCREW:
 35Ncm (3.1 in.LB)
 MAX. TORQUE: 68Ncm (6 in.LB)
 - SINGLE PACKED

* COMPLETELY TIGHTENED

Directive 2002/95/EC RoHS compliant

| | | | | | | |
|---|-------------------------------|----------|-----------------------------------|----------------------------|--------|-------------|
| THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND | tolerance | | dim. in mm | scale: | | 1,5:1 (1:1) |
| | ±0,3 unless thoerw. specified | | | material: | | SEE NOTES |
| | date | name | | title: | | |
| | drawn 06.02.2014 | Heinrich | | WATER RESISTANT D-SUB HOOD | | |
| | appd. 06.02.2014 | Huether | | 37 POS. | | |
| norm | | | JACKSCREW 4-40UNC STAINLESS STEEL | | | |
| d-old | | | dwg no: | | DIN-A3 | |
| a | Origin | | | 15K1A1434 | | sh: 1 |
| rev. | description | | | date | name | part no: |