



Capacitor value 1000 pF

Technical Characteristics

Materials:

Insulator: Thermoplastic UL94 V-0 black
 Contact: Copper alloy
 Contact finish: 0,2u Au over nickel
 Shell: steel tin plated

Characteristics:

Working voltage: 100 V
 Current rating: 5A
 Contact resistance: max. 10 MOHM
 Insulation resistance: > 1 GOHM
 Temperature range: -55° - 125°C

| General tolerances | | | | |
|--------------------|---------------|-------------|--------------|----------------|
| tolerances | ± 0,1 | ± 0,2 | ± 0,2 | ± 0,3 |
| size (mm) | > 0,5 up to 3 | > 3 up to 6 | > 6 up to 30 | > 30 up to 120 |

| | | | | | | | | | | |
|-----|------|------|----|--|---------------|-------------------------|------------------------|----------|--|------|
| | | | | | | | | | | |
| | | | | Date | Name | DESCRIPTION | | | | |
| | | | | Drawn | 09-08-31 | Jelisarow | DSubFilter | | | |
| | | | | Checked | | | D-Sub Filter Adapter | | | |
| | | | | | | Scale | 1:1 | Position | | SIZE |
| | | | | Würth Elektronik eiSos GmbH & Co KG D-74638 Waldenburg Max-Eyth-Straße 1 | | Drawing.- No. 230016003 | | | | A4 |
| REV | FILE | DATE | BY | EDV NO | 230016003.dft | | System :Solid Edge V20 | | | |