



FHTxx^{*1)} P5Gy^{*2)}

e.g. FHT09P5G1

*1) xx No. of contacts 09, 15, 25 or 37

*2) y for performance classes 1, 2 or 3

(contact cycle for G1/G2/G3 = 500/200/50)

xx	A (mm)	B (mm)	C (mm)	*øE (mm)	*H (mm)	*J (mm)
09	30,8	16,9	25	ø 1	9,4	2,54
15	39,1	25,2	33,3			
25	53	38,9	47,04			
37	69,3	55,3	63,5			

*PCB hole patterns, øE, H, J on supplement AM0024

No.	St.	Part	Type	Description/Material	Surface plating/Colour/Class
4	2	Clinch nut	FT 4-40 / Steel		tin plated
3	xx	Signal contact	P5 / Brass		G1/G2/G3
2	1	Shell	Steel		tin plated
1	1	Insulator	PCT (-55°C - +150°C)		natural

No.	St.	Part	Type	Description/Material	Surface plating/Colour/Class

REV.	DATE	CH.-NO.	ORIGINAL: DIN A3-DRAWING AS A FILE	REPLACEMENT FOR:	PAGES
1					1

COMMENT:
ALL RIGHTS ARE RESERVED BY US FOR THIS DRAWING. WITHOUT OUR PRIOR CONSENT,
THIS DRAWING IS NOT TO BE REPRODUCED, COPIED, STORED IN A RETRIEVABLE SYSTEM,
AND IT ALSO MAY NOT BE IMPROPERLY USED BY THE RECEIVER, OR A THIRD PARTY.



Measurement without tolerance acc. to ISO 2768-m

SCALE 2:1

TITLE

D-Sub Miniature Connector

DRAWN 19-11-2004 sschref
CHECKED 19-11-2004 ffo8mann

FCT group
www.fctgroup.com

DWG.NO.

FHTxxP5Gy

REV.

1

REPLACEMENT FOR:

PAGES 1