

APPLICABLE STANDARD						
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C		
	OPERATING & STORAGE HUMIDITY RANGE	85%MAX	VOLTAGE	AC 125V		
			CURRENT	0.5 A		
SPECIFICATIONS						
ITEM	TEST METHOD	REQUIREMENTS	QT	AT		
CONSTRUCTION						
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X		
MARKING	CONFIRMED VISUALLY.		X	X		
ELECTRICAL CHARACTERISTICS						
CONTACT RESISTANCE	100 mA (DC OR 1000 Hz).	65 mΩ MAX. (SIGNAL) 1	X	X		
INSULATION RESISTANCE	100 V DC.	1000 MΩ MIN.	X	—		
VOLTAGE PROOF	250 V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	X	X		
MECHANICAL CHARACTERISTICS						
INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR.	INSERTION FORCE 25N MAX. WITHDRAWAL FORCE 2.6 N MIN.	X	—		
MECHANICAL OPERATION	1000 TIMES INSERTIONS AND EXTRACTIONS.	1) CONTACT RESISTANCE 85 mΩ MAX. 1 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	—		
VIBRATION	FREQUENCY 10 TO 55 Hz SINGLE AMPLITUDE 0.75 mm, 5 min/CYCLE, TOTAL 10 CYCLES.	1) NO ELECTRICAL DISCONTINUITY OF 10 μs. 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	—		
SHOCK	490 m/s ² DIRECTIONS OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.		X	—		
ENVIRONMENTAL CHARACTERISTICS						
THERMAL SHOCK	TEMP -55 →+5 TO +35 →+85 →+5 TO +35 °C TIME 30 → 5 → 30 → 5 min. UNDER 5 CYCLES.	1) CONTACT RESISTANCE: 85 mΩ MAX. 1 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	—		
HUMIDITY LIFE	TEMPERATURE 40 °C, HUMIDITY 90 TO 95 %, FOR 96 h	1) INSULATION RESISTANCE: 100 MΩ MIN. 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	—		
CORROSION SALT MIST	EXPOSED AT 5 % SALT WATER, FOR 48 h.	NO HEAVY CORROSION THAT LOSE FUNCTION.	X	—		
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	
REMARK			APPROVED	A0. SUZUKI	10.10.06	
1 EXCLUDES CONDUCTOR RESISTANCE OF CABLE. 2 EXAMINATION IS HELD WITH "DH-17-CV * B", "DH40-17S" AND "DH60-17P" OR "DH-17-CT * B", "DH40-17S" AND "DH60A-17P". Unless otherwise specified, refer to JIS C 5402 .			CHECKED	YH. ENAMI	10.10.06	
			DESIGNED	YH. MAMADA	10.10.01	
			DRAWN	YH. MAMADA	10.10.01	
			Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.
	SPECIFICATION SHEET		PART NO.	DH40-17S		
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL244-0054-0-00		1/1