

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					△				
△					△				
APPLICABLE STANDARD									
RATING	OPERATING TEMPERATURE RANGE	-40°C TO +85°C(95%RH MAX)			STORAGE TEMPERATURE RANGE	-40°C TO +85°C(95%RH MAX)			
	POWER	—W			CHARACTERISTIC IMPEDANCE	50Ω (0 TO 3 GHz)			
	PECULIARITY	—			APPLICABLE CABLE	—			
SPECIFICATIONS									
ITEM		TEST METHOD			REQUIREMENTS			QT	AT
CONSTRUCTION									
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.			ACCORDING TO DRAWING.			X	X
MARKING		CONFIRMED VISUALLY.						—	—
ELECTRIC CHARACTERISTICS									
CONTACT RESISTANCE		mA MAX (DC OR 1000 Hz).			CENTER CONTACT	mΩ MAX.		—	—
					OUTER CONTACT	mΩ MAX.		—	—
INSULATION RESISTANCE		250 V DC.			500 MΩ MIN.		X	—	
VOLTAGE PROOF		300 V AC FOR 1 min. CURRENT LEAKAGE 2mA MAX.			NO FLASHOVER OR BREAKDOWN.			X	—
VOLTAGE STANDING WAVE RATIO		FREQUENCY 0.045 TO 3 GHz.			VSWR 1.2 MAX.		X	—	
INSERTION LOSS		FREQUENCY TO GHz			dB MAX.		—	—	
MECHANICAL CHARACTERISTICS									
CONTACT INSERTION AND EXTRACTION FORCES		BY STEEL GAUGE.			EXTRACTION FORCE N		—	—	
		φ0.9017 ⁺⁰ / _{-0.0025} BY STEEL GAUGE.			EXTRACTION FORCE 0.3 N MIN.		X	—	
INSERTION AND WITHDRAWAL FORCES		MEASURED BY APPLICABLE CONNECTOR.			INSERTION FORCE N MAX.		—	—	
					EXTRACTION FORCE N MAX.		—	—	
MECHANICAL OPERATION		10000 TIMES INSERTIONS AND EXTRACTIONS. (400-600 cycles per hour)			① NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			X	—
VIBRATION		FREQUENCY TO Hz SINGLE AMPLITUDE mm, m/s ² AT CYCLES FOR DIRECTIONS.			① NO ELECTRICAL DISCONTINUITY OF μs. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			—	—
SHOCK		m/s ² DIRECTIONS OF PULSE ms AT TIMES FOR DIRECTIONS.						—	—
CABLE CLAMP ROBUSTNESS (AGAINST CABLE PULL)		APPLYING A PULL FORCE THE CABLE AXIALLY AT N MAX.			① NO WITHDRAWAL AND BREAKAGE OF CABLE. ② NO BREAKAGE OF CLAMP.			—	—
ENVIRONMENTAL CHARACTERISTICS									
DAMP HEAT, CYCLIC		EXPOSED AT TO °C, ~ % TOTAL CYCLES (h)			① INSULATION RESISTANCE: MΩ MIN. (AT HIGH HUMIDITY) ② INSULATION RESISTANCE: MΩ MIN. (AT DRY) ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			—	—
RAPID CHANGE OF TEMPERATURE		TEMPERATURE → → → °C TIME → → → min. UNDER CYCLES.			NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			—	—
CORROSION SALT MIST		EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.			NO HEAVY CORROSION.			X	—
REMARKS									
RoHS COMPLIANT				DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED	
				<i>n. Ninomiya</i>	<i>n. Ninomiya</i>	<i>m. Yamane</i>	<i>I. Mitani</i>		
Unless otherwise specified, refer to JIS C 5402.				'05.05.23	'05.05.23	'05.05.23	'05.05.24		
Note QT:Qualification Test AT:Assurance Test O:Applicable Test									
HRS HIROSE ELECTRIC CO., LTD.				SPECIFICATION SHEET			PART NO.		
							HRMJ-U. FLP-LA-3 (40)		
CODE NO.(OLD)		DRAWING NO.			PART NO.				
CL311.-0373-6-00		ELC4-300595-40			CL311-0373-6-40			1/1	

Apr.1.2017 Copyright 2017 HIROSE ELECTRIC CO., LTD. All Rights Reserved.

TO
RF

