



NOTES: UNLESS OTHERWISE SPECIFIED.

1. MATERIALS & FINISH:

- 1.1 HOUSINGS & NUTS: STAINLESS STEEL PASSIVATED.
- 1.2 CENTER CONTACT: GOLD PLATED BERYLLIUM COPPER
- 1.3 DIELECTRIC: PTFE (TEFLON)
- 1.4 GASKETS: SILICONE RUBBER
- 1.5 RETAINING RINGS: UNPLATED BERYLLIUM COPPER
- 1.6 SUPORT BEAD: NORYL

2. ELECTRICAL SPECIFICATIONS:

- 2.1 FREQUENCY RANGE: DC TO 18.0 GHZ
- 2.2 VSWR (MAX):
 - DC TO 4.0 GHZ: 1.04:1
 - 4.0 TO 8.0 GHZ: 1.07:1
 - 8.0 TO 18.0 GHZ: 1.12:1
- 2.3 IMPEDANCE: 50 OHMS

<p>This PROPRIETARY Document is property of Cinch Connectivity Solutions. It is confidential in nature, non-transferable, and issued with the clear understanding that it is not to be traded or copied without permission and is returnable upon demand.</p> <p>INTERPRET DRAWING IN ACCORDANCE WITH ASME Y14.5-2009.</p>	<p>3RD ANGLE PROJECTION</p>	MIDWEST MICROWAVE	
	<p>RoHS2 <input checked="" type="checkbox"/></p> <p>2011/65/EU</p>	<p>Title: ADAPTER N PLUG/3.5MM PLUG</p>	
<p>UNLESS OTHERWISE SPECIFIED UNITS: INCH</p> <p>.XX ±.02 .XXX ±.005 ANGLES ±2°</p>		<p>Model No. ADT-2712-NM-3MM-02-01</p>	
<p>Size A</p>	<p>DO NOT SCALE DRAWING</p>	<p>Date: 10/24/2014</p>	<p>Sheet 1 of 1</p>