



- Notes
- ① The recommended clamp torque of ref. No. ⑧ : 3 to 4 N·m. LOCTITE 243, HENKEL JAPAN or equivalent is recommended to prevent from loosening.
 - ② The recommended clamp torque of ref. No. ⑫ : 0.2 to 0.3 N·m. LOCTITE 243, HENKEL JAPAN or equivalent is recommended to prevent from loosening.
 - ③ This products to be used with cable clamp JR13WCC-*(73) * designate diameter of applicable cable.
 - ④ Rotation examples of ref. No. ⑥, ⑨ to ref. No. ① is shown.
 - ⑤ The cable pull and twisting strength, waterproof tightness and other characteristics may differ, depending on the cable structure. Please confirm before the use.

6	BRASS	NICKEL PLATING	12	STAINLESS STEEL	
5	NITRIL BUTADIENE RUBBER	(GRAY)	11	POLYACETAL	(WHITE)
4	PPS	(BLACK) UL94V-0	10	NITRIL BUTADIENE RUBBER	(GRAY)
3	PPS	(BLACK) UL94V-0	9	BRASS	NICKEL PLATING
2	COPPER ALLOY	SURFACE : GOLD PLATING 0.2μm min. UNDER : NICKEL PLATING 3μm min.	8	BRASS	NICKEL PLATING
1	BRASS	NICKEL PLATING	7	PHOSPHOR BRONZE	NICKEL PLATING
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
UNITS mm		SCALE 2 : 1	COUNT 	DESCRIPTION OF REVISIONS	DESIGNED
		APPROVED : HY. KOBAYASHI	18.02.22	DRAWING NO.	EDC-114785-32-00
HIROSE ELECTRIC CO., LTD.		CHECKED : HY. KOBAYASHI	18.02.22	PART NO.	RM15WTL-4S(32)
		DESIGNED : HY. KISHI	18.02.22	CODE NO.	CL109-1888-9-32
		DRAWN : MK. INOUE	18.02.08		